## BPU-2535-SI

*1 x 3.5" to 1 x 2.5" SATA I/II Hot-Swap Drive Cage*

### Features

- Support all 2.5" SATA I/II HDD/SSD
- Fit one 3.5" Drive Bay for 1 x 2.5" HDD
- With one SATA Power and one DATA Connector
- Support HDD Height from 9.5mm to 15mm
- Energy Saving on Using 2.5" HDD or SSD
- LED Indicators for Power & HDD access

### Specifications

| | |
|---|---|
| Hot Swap | 1x2.5"HDD |
| Standard Drive Bays | 3.5" Drive: 1 |
| Dimension (W x H x D) | 101 x 25 x 146 mm |
| Material | Plastic |
| HDD Interface | SATA I/II |
| Weight | 1 lb |

### Introduction

The BPU-2535-SI internal drive cage is a compact and cost effective solution for using an internal 3.5" drive cage for one 2.5" hard drive. The BPU-2535-SI is suitable for high performance 2.5" laptop SATA drives and it is easy and quick to install it into any tower case or rackmount chassis.

## BPU-2535V2

*1 x 3.5" to 2 x 2.5" SATA I/II Hot-Swap Drive Cage*

### Features

- Aluminum Frame
- Hard Drive Interface: SATA I/II
- Fit one 3.5" Drive Bay for 2 x 2.5" Hard Disk Drives (thickness: up to 9.5mm)
- Point to Point, Free from Master/ Slave Setting
- With one SATA Power and two DATA Connectors
- Energy Saving on Using 2.5" HDDs or SSD
- LED Indicators for Power & HDD access
- Security Key Lock
- RoHS Compliance

### Specifications

| | |
|---|---|
| Hot Swap | 2x2.5"HDD |
| Standard Drive Bays | 3.5" Drive: 1 |
| Dimension (W x H x D) | 3.98 x 0.98 x 5.91 inches |
| Material | Aluminum & Plastic |
| HDD Interface | SATA I/II |
| Weight | 1 lb |
| Packaging Information | Enclosure, Manual, Screws, Keys |

### Introduction

The BPU-2535V2 internal drive cage is a compact and cost effective solution for an internal 3.5" drive cage with two 2.5" hard drives. It provides an extra storage within a compact design to satisfy many application needs. The BPU-2535V2 is constructed of aluminum material that provides best heat dissipation required for high performance 2.5" laptop SATA drives. It is easy and quick to install it into any tower or rackmount chassis.